

iQ - Oval & iQ - Oval compact

Offering unbeatable versatility, expandability and operator safety, "this revolutionary oval press" with its intelligent chain-free drive system is the only serious choice for a growing business ...









FEATURES AND BENEFITS

Tablet main control unit with WIFI connectivity	•	MHM 'pin-lock' screen holding system •			
Self-diagnostic operating system	•	Adjustable screen holders for various frame sizes* •			
Instant technical support via internet	•	Individual screen lift (only screens in use move)			
Online software updates	•	Individual off-contact adjustment on all stations •			
Print job memory storage via main control unit	•	Full micro-registration with zero starting position •			
Revolutionary intelligent index drive system	•	Aluminium honeycomb pallets •			
Print start/finish and sample modes	•	Push button super-fast pallet changeover •			
Production/batch counter	•	Flash cure adjustments from main control unit •			
Skip/miss-loaded shirt button	•	Foot pedal with start and hold functions •			
Pre-heat pallets function	•	Wireless safety system •			
Powerful AC electric drive print heads	•	Adjustable index speed control	optional		
Control keypad on every print station	•	Laser positioning guides	optional		
Individual 'chopper' squeegee system	•	Smartphone / PC-app (links to tablet control)	optional		
Quick release squeegees & floodbars	•	U-clamp screen holders with pneumatic lock	optional		
Squeegee arm lift for increased visibility	•	Two job mode (print two jobs simultaneously) option			
Independent flood/print speed controls	•	High-lift stations for more flexibility option			
Tool-free front/rear stroke length adjustment	•	Power outlets (built-in) for flash / flock / foil optiona			
Independent squeegee/floodbar angle adjustment	•	Automatic 'GOTO' registration system with job optiona			
Squeegee pressure regulator on every station	•	memory (Safe the actual screen positions for unlimited jobs)			

 * All MHM machines are compatible with both standard and re-tensionable roller frames.



Specifications	45 x 55 cm	50 x 70 cm	70 x 100 cm	80 x 110 cm		
Number Number of pallets	up to 60					
Max. number of print stations	up to 29					
Max. print area (cm / inch)	45 x 55 cm / 17.7 x 21.7"	50 x 70 cm / 19.7 x 27.6"	70 x 100 cm / 27.6 x 39.4"	80 x 110 cm / 31.5 x 43.3"		
Width of machine (cm / inch)	370 cm / 145.7"	400 cm / 157.5"	420 cm / 165.4"	440 cm / 173.2"		
Length of basic element (cm / inch)	640 cm / 252"	730 cm / 287.4"	790 cm / 311"	810 cm / 318.9"		
Length of 2-step-section (cm / inch)	190 cm / 74.8" 260 cm / 102.4"					
Length of 3-step-section (cm / inch)	285 cm / 112.2"	n / 112.2" 390 cm / 153.5"				
Weight of basic element (kg / lbs)	1190 / 2620	1345 / 2970	1390 / 3060	1420 / 3130		
Weight of 2-step-section (kg / lbs)	500 / 1100	595 / 1300	615 / 1360	630 / 1390		
Weight of 3-step-section (kg / lbs)	750 / 1650	890 / 1960	920 / 2030	940 / 2070		
Weight of station (kg / lbs)	90 / 198.5	100 / 220.5	100 / 220.5	110 / 242.5		
Air consumption per printstation (I/min)	30 (1.06 cfm)					
Air consumption per table (I/min)	15 (0.53 cfm)					
Air pressure (minimum)	8 bar / 116 psi (filtered, dry air supply only)					
Drive System	iDS intelligent drive system (individual drive on every pallet arm)					
Electrical supply	3 ph-210 / 400 V, 50 / 60Hz (+/-5%)					
Electrical requirement (per print station)	0.4 kW / 0.6 kW (manual / automatic)					
Electrical requirement (per pallet)	0.11 kW					
Registration accuracy (mm / inch)	+/- 0.02 mm / +/-0.00079"					
Rec. frame profile (cm / inch)	4 x 4 cm / 1.57 x 1.57"					
Max. frame size (cm / inch)	66 x 100 cm / 26 x 39.4"	105 x 115 cm / 41.3 x 45.2"	105 x 144 cm / 41.3 x 56.7"	105 x 154 cm / 41.3 x 60.6"		
Max. production capacity (pieces/h)	1200 - 1800 (according to model / 2 job mode)					